


**Product Name:** GT Splash  
**Model Number:** 6257SP  
**Size:** Length: 31' 6"  
 Width: 14' 5"  
 Height: 9' 7"  
**Fall Height:** 10'  
**Foundations:** 15  
**Concrete Volume:** 4.7 cubic yards  
**COMPLIANT WITH:** ASTM F-1487  
 CSA Z614  
**Ages:** 5-12 years  
**Use Zone:** Length: 43' 6"  
 Width: 26' 5"



**Technical Details:**

**Climber Frame**

Main curvilinear supports shall be 5-1/2" (140mm) diameter steel tubing combined with 3-1/2" (89mm) and 2-3/8" (61mm) diameters steel tubing. After fabrication the frame shall be powder coated in accordance with the specifications herein.

**Climber Pipe Junctions**

8" (200mm) and 12" (300mm) diameters structural aluminum covers with integrated sleeves for pipe connections provided and shall be powder coated in accordance with the specifications herein.

**Rope**

20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.

**Rope Ball Connectors and End Fittings**

One-piece compressed aluminum ball connector or end fitting, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.

**Decking**

Shall be made from min. 3/4" (19mm) thick high density, UV-stabilized and color impregnated polyethylene.

**Flexible Surfaces**

5/16"(8mm) thick textile-reinforced rubber belt.

**Fasteners**

All fasteners shall be stainless steel with locking patch or locking compound (by others).

**Rotationally molded slide and climbers**

Shall be uniform construction with rotationally molded linear low-density U.V. stabilized polyethylene with a 1/4" (6mm) nominal wall thickness, available in manufacturer's standard colors.

**Slide Support**

Shall be fabricated 2" (50mm) galvanized steel tubing with a formed 11 gauge (3mm) steel plate and shall be powder coated in accordance with the specifications herein.

**Metal Finish**

Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electrostatic method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection.

**Installation**

Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.

**Concrete Achors**

Supplied by others.