


**Product Name:** VistaTwist 3 w/ VistaTree House  
**Model Number:** 6679SP  
**Size:** Length: 26' 4"  
 Width: 23' 6"  
 Height: 18' 8"  
**Fall Height:** 10'  
**Foundations:** 9  
**Concrete Volume:** 3.6 cubic yards  
**COMPLIANT WITH:** ASTM F-1487  
 CSA Z614  
**Ages:** 5-12 years  
**Use Zone:** Length: 39' 3"  
 Width: 35' 6"



#### Technical Details:

##### Climber Frame

Main curvilinear supports shall be 4-1/2" (114 mm) diameter steel tubing combined with 2-3/8" (61mm) diameters steel tubing. After fabrication the frame shall be powder coated in accordance with the specifications herein.

##### Climber Pipe Junctions

8" (200mm) and 12" (300mm) diameters structural aluminum covers with integrated sleeves for pipe connections provided and shall be powder coated in accordance with the specifications herein.

##### Rope

20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.

##### Rope Ball Connectors and End Fittings

One-piece compressed aluminum ball connector or end fitting, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.

##### Decking

Shall be made from min. 3/4" (19mm) thick high density, UV-stabilized and color impregnated polyethylene.

##### Flexible Surfaces

5/16" (8mm) thick textile-reinforced rubber belt.

##### Fasteners

All fasteners shall be stainless steel with locking patch or locking compound (by others).

##### Rotationally molded slide and climbers

Shall be uniform construction with rotationally molded linear low-density U.V. stabilized polyethylene with a 1/4" (6mm) nominal wall thickness, available in manufacturer's standard colors.

##### Slide Support

Shall be fabricated 2" (50mm) galvanized steel tubing with a formed 11 gauge (3mm) steel plate and shall be powder coated in accordance with the specifications herein.

##### Metal Finish

Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electro-static method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection.

##### Installation

Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.

##### Concrete Achors

Supplied by others.